



A **HAVELLS** Brand




MAKE YOUR
COMMERCIAL SPACE
THE COOLEST PLACE
TO WORK OR CHILL!

LLOYD AIR CONDITIONING SOLUTIONS
FOR COMMERCIAL SPACES

TOWER AC



GLT48B01AG



Simple & Elegant Design

The modern and unique design of this Lloyd air conditioner delivers a premium and sleek look.



Touch Control

The control buttons are embedded into the body so that the unit can be controlled only with a gentle touch.



Smart 4-Way Swing

With the Smart 4-Way swing through horizontal and vertical louvers, the AC spreads cool air uniformly throughout the room, and makes room cool and comfortable.



Easy Clean Filter

The air inlet grill and filter are easy to remove, making the cleaning process much easier.



Low Noise

Optimised duct and turbine design makes the air conditioner much quieter during its operation.



Side Air Inlet

Uniquely designed side air inlet makes this unit much more appealing and easier to clean.

MODEL FAMILY		TOWER AC	
MODEL NO.		GLT24B22MT	GLT48B01AG
PARAMETERS	Unit		
HIGHLIGHTS			
ITEM DESCRIPTION		2.0	4.0
STAR RATING		2	NA
COMP. TYPE		ROTARY	SCROLL
REFRIGERANT		R 32	R-410A
ELECTRIC DATA			
POWER SUPPLY	V-Hz-Ph	220 V~240 V/ 50 Hz /1 Phase	380 V~415 V/ 50 Hz /3 Phase
INPUT CURRENT	Amps	8.11 A	9.02 A
PERFORMANCE			
COOLING CAPACITY	Watts	6250 W	13500 W
INPUT POWER	Watts	1838 W	5490 W
ISEER		3.4	NA
AIR FLOW	m3/h	800 m3/h	1680 m3/h
ELECTRICITY CONSUMPTION	kWh	1422.81 kWh	4249.85 kWh
IDU NOISE	dB	57 dB	52 dB
ODU NOISE	dB	70 dB	64 dB
WEIGHT & MEASUREMENT			
IDU DIM. (LXBXH)	cm	(50.6 × 31.5 × 178.0) cm	(55.0 X 35.0 X 180.0) cm
IDU PACKING (LXBXH)	cm	(62.0 × 46.0 × 197.0) cm	(68.5 X 46.5 X 191.0) cm
IDU NET / GROSS WEIGHT	kg	39.0 kg / 45.0 kg	50.7 kg / 62.6 kg
ODU DIM. (LXBXH)	cm	(85.0 X 31.0 X 68.4) cm	(94.6 X 41.0 X 81.0) cm
ODU PACKING (LXBXH)	cm	(98.0 X 42.5 X 75.5) cm	(109.0 X 50.0 X 87.5) cm
ODU NET / GROSS WEIGHT	kg	39.5 kg / 44.5 kg	81.2 kg / 86.0 kg



Auto Restart

On restoration of power after a sudden power failure, the AC will restart automatically and will operate based on the previous setting.



Golden Fin

The innovative anti-corrosion coating in the fin helps to prevent bacteria and enhances the efficiency of heat transfer.




Self-Diagnosis & Auto-Protection

In case of abnormal operation, the unit will protect the system by shutting down automatically. Meanwhile, the error code enables engineers to identify the problem quickly.



GLT24B22MT

CASSETTE AC



Instant Cooling

Compared with the fixed-speed air conditioner, full DC inverter air conditioner increases its cooling speed by around 30%. It takes only 10 minutes to lower the room temperature 36 °C to 30 °C when the outdoor temperature is as high as 43°C.



Precision Temperature Control

Full DC inverter air conditioners outperform fixed-speed air conditioners in the aspect of precision temperature control.

MODEL FAMILY		FIXED SPEED CASSETTE AC			INVERTER CASSETTE AC		
MODEL NO.		GLC24B11AC	GLC36B01AC	GLC48B01AC	LC24I32AC	LC36I02AC	LC48I02AC
PARAMETERS	UNIT						
HIGHLIGHTS							
ITEM DESCRIPTION		2.0	3.0	4.0	2.0	3.0	4.0
STAR RATING		1	NA	NA	3	NA	NA
COMP. TYPE		ROTARY	ROTARY	SCROLL	ROTARY	ROTARY	ROTARY
REFRIGERANT		R-32	R-410A	R-410A	R-32	R-32	R-32
ELECTRIC DATA							
POWER SUPPLY	V-Hz-Ph	220 V~240 V/50 Hz / 1 Phase	380 V~415 V/50 Hz/ 3 Phase	380 V~415 V/50 Hz / 3 Phase	220 V~240 V/50 Hz / 1 Phase	380 V~415 V/50 Hz / 3 Phase	380 V~415 V/50 Hz / 3 Phase
INPUT CURRENT	Amps	9.97 A	6.6 A	8.91 A	9.58 A/4.35 A	6.43 A/2.19 A	8.82 A/2.79 A
PERFORMANCE							
COOLING CAPACITY	Watts	7050 W	10600 W	13500 W	6950/3475 W	10550/5275 W	13000/6500 W
INPUT POWER	Watts	2258 W	3700 W	5300 W	2170/850 W	3960/1350 W	5430/1720 W
ISEER		3.12	NA	NA	3.92	NA	NA
AIR FLOW	m3/h	1550 m3/h	1700 m3/h	1600 m3/h	1200 m3/h	1800 m3/h	1800 m3/h
ELECTRICITY CONSUMPTION	kWh	1747.93 kWh	2864.19 kWh	4102.77 kWh	1373.83 kWh	2325.34 kWh	3066.53 kWh
IDU NOISE	dB	40 dB	53 dB	54 dB	46/40/37 dB	55/49/46 dB	55/49/45 dB
ODU NOISE	dB	62 dB	64 dB	64 dB	57 dB	59 dB	61 dB
WEIGHT & MEASUREMENT							
IDU DIM. (LXBXH)	cm	(84.0 X 84.0 X 24.5) cm	(84.0 X 84.0 X 24.5) cm	(84.0 X 84.0 X 24.5) cm	(84.0 X 84.0 X 20.5) cm	(84.0 X 84.0 X 24.5) cm	(84.0 X 84.0 X 24.5) cm
IDU PACKING (LXBXH)	cm	(90.0 X 90.0 X 25.7) cm	(90.0 X 90.0 X 25.7) cm	(90.0 X 90.0 X 25.7) cm	(90.0X90.0X22.5) cm	(90.0 X 90.0 X 26.5) cm	(90.0 X 90.0 X 26.5) cm
IDU NET / GROSS WEIGHT	kg	25.6 kg / 30.9 kg	24.7 kg / 28.4 kg	27 kg / 30.5 kg	22.6 kg / 27.3 kg	25.4 kg / 30.5 kg	27.7 kg / 32.7 kg
ODU DIM. (LXBXH)	cm	(84.5 X 36.3 X 70.2) cm	(94.6 X 41.0 X 81.0) cm	(94.6 x 41.0 x 81.0) cm	(89.0 X 34.2 X 67.3) cm	(94.6 x 41.0 x 81.0) cm	(94.6 x 41.0 x 81.0) cm
ODU PACKING (LXBXH)	cm	(96.5 X 39.5 X 76.5) cm	(109.0 X 50.0 X 87.5) cm	(109.0 x 50.0 x 87.5) cm	(100.0 X 41.5 X 75.0) cm	(109.0 x 50.0 x 87.5) cm	(109.0 x 50.0 x 87.5) cm
ODU NET / GROSS WEIGHT	kg	48.4 kg / 51.8 kg	68.3 kg / 72.9 kg	81.2 kg / 86 kg	38.2 kg / 41.5 kg	66.9 kg / 71.5 kg	72.4 kg / 77.2 kg



Cool Surround 360 °C

The cassette's airflow design allows cool air to diffuse and sink evenly, offering uniform cooling experience throughout the space.



Twin System with Sync Control

The twin system connects 2 IDUs of the same type and capacity to 1 ODU for more air distribution in a large room. The controller can operate both IDUs simultaneously.



Fresh Air

Fresh air from outside can be led into the room through a connection pipe, which keeps the indoor air fresh and healthy.



Flexi Wind Control

The 4 air outlets can be independently controlled for customised comfort.



HAVELLS INDIA LIMITED

QRG TOWERS, 2D, SECTOR 126, EXPRESSWAY, NOIDA - 201304, U.P. (INDIA)

Tel.: +91-120-3331000 | **Fax:** +91-120-3332000

For customer care services, please write to: perfectservice@lloydmail.com

For corporate sales enquiry, write to: sales@lloydmail.com

Customer Care No.: 0804-577-5666

— VISIT US AT: WWW.MYLLOYD.COM —

Copyrights subsists. Imitation of trade dress, graphics and color scheme of this document is a punishable offence. E&OE. Product feature and specification may vary $\pm 5\%$. Product Feature and specification may change from time to time for product improvement and development. Kindly refer to product manual for more information. Noise level reflects the level in Anechoic chamber. Images used are for reference only actual product may vary.



Air conditioners falls under e-waste category. Don't mix electronic waste with other waste, for proper disposal of e-waste kindly visit www.mylloyd.com/about-us/social-initiatives